

# GIRA downlight

MOVE IT 10  
030-6410638M



Project / Type


Notes

Count / Date




Linear light inset made of aluminium; surface jet black powder coated; light inset 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; fitted with single LED light points; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 23° beam; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

## Light distribution



medium 23°			
h (m)	EO° (lx)	ø (m)	
1	4630	0.40	
2	1160	0.80	
3	510	1.20	
4	290	1.61	
5	190	2.01	

## Product drawing



### General

rotation 360°

jet black , RAL9005 <sup>1</sup>

IP20

1170 lm

### LED

4000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 94 , R<sub>f</sub>: 87 , R<sub>(1-15)</sub>: 90

MR 0.86

MDER 0.78

### Optical

Medium

beam angle 23°

### Electrical

DALI-2

18.2 W

PC3

64 lm/W

1 DALI Addr.

### Physical

length 217 mm

width 19 mm

height 19 mm

<sup>1</sup> RAL code

## Installation instructions

