

GIRA downlight

MOVE IT 10

030-6410437M



Project / Type


Notes

Count / Date



Linear light inset made of aluminium; surface traffic white powder coated; light inset 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; fitted with single LED light points; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 23° beam; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



medium 23°

h (m)	EO° (lx)	ø (m)
1	4310	0.40
2	1080	0.80
3	480	1.20
4	270	1.61
5	170	2.01

Product drawing



General

rotation 360°

traffic white , RAL9016 ¹

IP20

1090 lm

LED

2700 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_f: 91 , R₍₁₋₁₅₎: 89

MR 0.54

MDER 0.49

Optical

Medium

beam angle 23°

Electrical

DALI-2

18.2 W

PC3

60 lm/W

1 DALI Addr.

Physical

length 217 mm

width 19 mm

height 19 mm

¹ RAL code

Installation instructions



[“030-6410437M”] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com