

SPOT LINE

MOVE IT 10


030-6110438M



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling / Wall , Track _____

jet black , RAL9005 ¹ _____

IP20 _____

575 lm _____

LED

2700 K _____

CRI \geq 90 _____

L80 / 50000 h _____

initial MacAdam \leq 3 SDCM _____

R_g: 99 , R_f: 93 , R₍₁₋₁₅₎: 91 _____

MR 0.52 _____

MDER 0.47 _____

Optical

Medium _____

UGR < 13 , \geq 65° <1500 cd/m² _____

Electrical

DALI-2 _____

6.6 W _____

PC3 48V _____

87 lm/W _____

1 DALI Addr. _____

Physical


length 300 mm _____

width 11 mm _____


height 10 mm _____

Linear light inset made of plastic; surface jet black; light inset can be installed and moved without tools by means of clip mount; flush with profile system; power supplied via MOVE IT system track profile; hot plug protection; fitted with single LED light points; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; recessed light point plane; inserted lenses with medium radiation characteristic; UGR \leq 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° \leq 1500 cd/m²; degree of protection IP20; PC3 48V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

Light distribution



Product drawing



¹ RAL code

Installation instructions

