

MOVE IT 10 track round suspended /

pole
030-1417038



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

jet black , RAL 9005 ¹

IP20

Electrical

DALI-2

48 V

PC3

Physical

length 3100 mm

width 29 mm

height 26 mm

1.96 kg

¹ RAL code

Installation
instructions



Thin extruded aluminium profile with 26 mm height and 10 mm width groove; tubular design; for vertical, horizontal or suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; surface anodised jet black; with integrated power track profile on both sides for take off of supply voltage and DALI-2 signal; power supply and DALI-2 signal for both power tracks with only one feed by means of PASS THROUGH connector (as an accessory); light insets can be installed and moved without tools by means of clip mount; degree of protection IP20; PC3; 48 V; accessories are listed separately;

Product drawing



[‘030-1417038’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com