



Project / Type _____

Notes _____

Count / Date _____



Linear light inset made of aluminium; surface white powder coated; for VITA system module; lighting module with specially computed, asymmetrical high gloss reflector, linear prismatic cover incl. foil; designed for use as direct light component; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; with 2 plug-in terminals for through wiring; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



General

Wall | Surface _____

white | RAL 9010 ¹ _____

IP20 _____

7240 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 | R_f: 91 | R_{f(1-15)}: 89 _____

MR 0.61 | MDER 0.55 _____

Optical

Linear Prismatic | asymmetric _____

PstLM ≤ 1.0 ² | SVM ≤ 0.4 ² _____

Electrical

DALI-2 | 1 DALI Addr. _____

PC1 | 220-240 V _____

system 65 W _____


system 111 lm/W ³ _____

Physical


length 1006 mm | width 45 mm | height 22 mm _____

0.87 kg _____

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

