



Project / Type _____

Notes _____

Count / Date _____



General

Wall , Surface _____

white , RAL9010 ¹ _____

IP20 _____

7240 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

photobio. safety RG 0 - no Risk _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89 _____

MR 0.61 _____

MDER 0.55 _____

Optical

Linear Prismatic _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

65 W _____

PC1 220-240V _____

111 lm/W _____

1 DALI Addr. _____

Physical

length 1006 mm _____


width 45 mm _____

height 22 mm _____


1.7 kg _____

Linear light inset made of aluminium; surface white powder coated; for VITA system module; lighting module with specially computed, asymmetrical high gloss reflector, linear prismatic cover incl. foil; designed for use as direct light component; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; degree of protection IP20; PC1 220-240V; with 2 plug-in terminals for through wiring; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions

