

VARO 80 S

track
180-6422138F



Project / Type _____

Notes _____

Count / Date _____



Track light made of die-cast aluminium; surface black powder coated; 355° rotatable and 90° tiltable; integrated converter in the plastic adapter; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; including high quality aluminium reflector with spherical reflector; high gloss anodised; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 39° beam; installed and exchanged without tools; optical attachments available as accessories; optical attachments can be combined; accessories are listed separately; degree of protection IP20; PC2 220-240V; incl. DALI-2 converter; adapter for toolless insertion or movement on a variety of 3-phase power tracks; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

220-240V

220-240V

X-PERT

X-PERT

General

Ceiling , Track

tilt max 90°

rotation 355°

black , RAL9005 ¹

IP20

2800 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

Optical

flood

beam angle 39°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

21.1 W

PC2 220-240V

133 lm/W

1 DALI Addr.


Physical

diameter 87 mm

height 80 mm


0.5 kg

Light distribution



flood 39°			
h (m)	E0° (lx)	ø (m)	
1	5750	0.70	
2	1440	1.40	
3	640	2.10	
4	360	2.80	
5	230	3.50	

Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

