



VITA

wall

EN Luminaire housing, mounting channel and front cover from extruded aluminium profile, angular version; extremely slim luminaire housing (only 25 mm), for direct/indirect radiation characteristic; no visible screws; surface anodised; suitable for wall mounting; lighting modules with specially computed, asymmetrical high gloss reflectors, linear prismatic covers incl. foil with different light distributions for optimised light control and homogeneous illumination; lighting modules in aluminium, powder coated; CRI ≥ 90 or XPECTRUM; incl. 2 converters for separate control of the direct/indirect light component; energy-efficient LEDs with very good colour rendering


DE Leuchtenkörper, Montagekanal und Frontabdeckung aus Aluminiumstrangpressprofil, kantige Ausführung; extrem schlanker Leuchtenkörper (nur 25 mm), für direkt/indirekte Abstrahlcharakteristik; keine sichtbaren Schrauben; Oberfläche eloxiert; geeignet für Wandmontage; Lichteinsätze mit speziell berechneten, asymmetrischen Hochglanz-Reflektoren, linearprismatische Abdeckungen inkl. Folie mit unterschiedlicher Lichtverteilung für Direkt- bzw. Indirektlichtanteil zur optimierten Lichtlenkung und homogenen Ausleuchtung; Lichteinsätze aus pulverbeschichtetem Aluminium; CRI ≥ 90 oder XPECTRUM; inkl. 2 Konverter zur getrennten Steuerung des Direkt-/Indirektlichtanteils; energieeffiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo


3000 K, 4000 K
CRI ≥ 90 , CRI ≥ 97 XPECTRUM
up to 121 lm/W
L80/85 @ 50 000 h
DALI-2
linear prismatic

Types

horizontal mounting




vertical mounting




Colour



Light distributions



system
solution



CRI ≥ 97
XPECTRUM

Order options

COLOUR TEMPERATURE	☑☑
3000 K (CRI ≥ 90)	0
4000 K (CRI ≥ 90)	1
3000 K (CRI ≥ 97 XPECTRUM)	Y
4000 K (CRI ≥ 97 XPECTRUM)	Z

CONTROL

DALI-2

direct/indirect separately controllable

MATERIAL COLOUR

● anodised aluminium

LIGHT INSET COVER

linear prismatic

Options on request

COLOUR TEMPERATURE


tunable white (2700–6500 K)

MATERIAL COLOUR

white, black, special colours

SPOTLIGHT ALIGNMENT

SPOTLIGHT for reading




VITA wall



DIRECT/INDIRECT - HORIZONTAL MOUNTING


SYS. POWER	LUMINOUS FLUX	L (mm)	ORDER CODE
123 W	↓ 7460 / ↑ 7460 lm	1013	099-9136::36A
158 W	↓ 8950 / ↑ 8950 lm	1213	099-9137::36A



DIRECT/INDIRECT - VERTICAL MOUNTING

SYS. POWER	LUMINOUS FLUX	L (mm)	ORDER CODE
123 W	↓ 7460 / ↑ 7460 lm	1013	099-9166::36A
158 W	↓ 8950 / ↑ 8950 lm	1213	099-9167::36A

Light distribution



asymmetric linear prismatic
direct/indirect

LUMINOUS FLUX value calculated for

4000 K, CRI ≥ 90, white;
3000 K CRI90-9%, 3000 K CRI97 -24%,
4000 K CRI97 -22%