

VITA vertical 1213 direct / indirect

wall
099-9167036A



Project / Type

Notes

Count / Date



General

Wall , Surface

anodised aluminium

IP20

indirect 8670 lm

direct 8670 lm

total 17340 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89

MR 0.61

MDER 0.55

Optical


Linear Prismatic

PstLM ≤ 1.0 ¹


SVM ≤ 0.4 ¹

Luminaire housing, mounting channel and front cover from extruded aluminium profile; angular design; no visible screws; surface anodised aluminium; suitable for wall mounting; equipped with two light insets made of aluminium, powder coated; direct/indirect illumination characteristic; lighting modules with specially computed, asymmetrical high gloss reflectors, linear prismatic covers incl. foil with different light distributions for direct or indirect light component for optimised light control and homogeneous illumination; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; direct/indirect light component separate controllable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Electrical

DALI-2

148 W

PC1 220-240V

117 lm/W

2 DALI Addr.

Physical

length 1213 mm

width 160 mm

height 70 mm

3 kg

¹ Value of containing product at full load (undimmed)

Installation instructions

