



Project / Type

Notes

Count / Date




General
Wall , Surface
anodised aluminium
IP20
indirect 5850 lm
direct 5850 lm
total 11700 lm

LED
4000 K
CRI ≥ 97
L85 / 50000 h
photobio. safety RG 0 - no Risk
initial MacAdam ≤ 3 SDCM
R _g : 100 , R _f : 96 , R ₍₁₋₅₎ : 98
MR 0.86
MDER 0.78


Optical
Linear Prismatic
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Luminaire housing, mounting channel and front cover from extruded aluminium profile; angular design; no visible screws; surface anodised aluminium; suitable for wall mounting; equipped with two light insets made of aluminium, powder coated; direct/indirect illumination characteristic; lighting modules with specially computed, asymmetrical high gloss reflectors, linear prismatic covers incl. foil with different light distributions for direct or indirect light component for optimised light control and homogeneous illumination; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; direct/indirect light component separate controllable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Electrical
DALI-2
123 W
PC1 220-240V
95 lm/W
2 DALI Addr.

Physical
length 1013 mm
width 160 mm
height 70 mm
1.7 kg

¹ Value of containing product at full load (undimmed)

Installation instructions

