



Project / Type _____


Notes _____

Count / Date _____




Luminaire housing, mounting channel and front cover from extruded aluminium profile; angular design; no visible screws; surface anodised aluminium; suitable for wall mounting; equipped with two light insets made of aluminium, powder coated; direct/indirect illumination characteristic; lighting modules with specially computed, asymmetrical high gloss reflectors, linear prismatic covers incl. foil with different light distributions for direct or indirect light component for optimised light control and homogeneous illumination; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; incl. DALI-2 converter; direct/indirect light component separate controllable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Wall , Surface _____

anodised aluminium _____

IP20 _____

indirect 5850 lm _____

direct 5850 lm _____

total 11700 lm _____

11700 lm/m _____

LED

4000 K _____

CRI ≥ 97 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 100 , R_f: 96 , R_{f(1-5)}: 98 _____

MR 0.86 _____

MDER 0.78 _____

Optical

Linear Prismatic _____

asymmetric _____

PstLM ≤ 1.0 ¹ _____

SVM ≤ 0.4 ¹ _____

Electrical

DALI-2 _____

220-240 V _____

system 123 W _____

system 95 lm/W² _____

PC1 _____

2 DALI Addr. _____

123 W/m _____

Physical

length 1013 mm _____

width 160 mm _____

height 70 mm _____

¹ Value of containing product at full load (undimmed)
² incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



VITA vertical 1013 direct / indirect
wall
099-9166Z36A



Project / Type

Notes

Count / Date

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	6
B13	8
B16	10
B20	13
C10	10
C13	14
C16	17
C20	22

