



Project / Type _____

Notes _____

Count / Date _____



General

Wall , Surface _____

anodised aluminium _____

IP20 _____

indirect 8950 lm _____

direct 8950 lm _____

total 17900 lm _____

LED

4000 K _____

CRI \geq 90 _____

L80 / 50000 h _____

photobio. safety RG 0 - no Risk _____

initial MacAdam \leq 3 SDCM _____

R_g: 98 , R_r: 90 , R_{t(1-15)}: 88 _____

MR 0.76 _____

MDER 0.69 _____

Optical


Linear Prismatic _____

PstLM \leq 1.0 ¹ _____


SVM \leq 0.4 ¹ _____

Luminaire housing, mounting channel and front cover from extruded aluminium profile; angular design; no visible screws; surface anodised aluminium; suitable for wall mounting; equipped with two light insets made of aluminium, powder coated; direct/indirect illumination characteristic; lighting modules with specially computed, asymmetrical high gloss reflectors, linear prismatic covers incl. foil with different light distributions for direct or indirect light component for optimised light control and homogeneous illumination; light colour 4000 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; direct/indirect light component separate controllable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Electrical

DALI-2 _____

148 W _____

PC1 220-240V _____

121 lm/W _____

2 DALI Addr. _____

Physical

length 1213 mm _____

width 130 mm _____

height 55 mm _____

3 kg _____

¹ Value of containing product at full load (undimmed)

Installation instructions

