

# MOVE IN 45 flex round

trim

063-8221514V 063-8822117 002-90726



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



**General**

Ceiling | Semi-Recessed

tilt max 90°

rotation 360°

chrome

Mounting set traffic white

IP20

346 lm

fixture 50 lm/W <sup>1</sup>

**LED**

3000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 98 | R<sub>f</sub>: 91 | R<sub>f(-15)</sub>: 89

MR 0.6 | MDER 0.55

**Optical**

super spot | beam angle 8°

PstLM ≤ 1.0 <sup>2</sup> | SVM ≤ 0.4 <sup>2</sup>

**Electrical**

non DIM

PC2 | 220-240 V

system 9.2 W | fixture 6.9 W

11 Vf | 600 mA

**Physical**

trim

diameter 77 mm | height 107 mm

0.58 kg


## Light distribution



super spot 8°

h (m)	EO° (lx)	ø (m)
1	12100	0.14
2	3000	0.28
3	1300	0.41
4	800	0.55
5	500	0.69

## Product drawing



**Cutout**

diameter 65 mm

min. ceiling thickness 2 mm | max. ceiling thickness 25 mm

recessed depth 200 mm

<sup>1</sup> incl. consideration of optical losses & internal control unit losses

<sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions

## Lighting calculator

