

# MOVE IN 45 flex round

trimless

063-8221514M 063-8812117 002-90724



Project / Type
Notes
Count / Date



Round spotlight element in aluminium; surface chrome; installation without tools in mounting set due to patented ball catch system; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 9-25 mm; special mounting tool for easy installation of the trimless housing available as an accessory; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; 360° rotatable and 90° tiltable; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality, aluminium, vapour deposition coated reflector with faceted lens design; precise radiation characteristic with 24° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC2; 220-240 V; incl. converter, non dimmable; converter wired secondary side; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



medium 24°

h (m)	EO° (lx)	ø (m)
1	6120	0.43
2	1530	0.86
3	680	1.30
4	380	1.73
5	240	2.16

## Product drawing



## General

Ceiling   Semi-Recessed
tilt max 90°
rotation 360°
chrome
Mounting set traffic white
IP20
1270 lm

## LED

3000 K
CRI $\geq 90$
L80 / 50000 h
initial MacAdam $\leq 2$ SDCM
R <sub>g</sub> : 100   R <sub>f</sub> : 91   R <sub>f(1-5)</sub> : 89
MR 0.59   MDER 0.53

## Optical

medium   beam angle 24°
PstLM $\leq 1.0$ <sup>1 2 3 4</sup>   SVM $\leq 0.4$ <sup>1 2 3 4</sup>

## Electrical

non DIM
PC2   220-240 V
system 15.9 W   fixture 13.5 W
fixture 95 lm/W <sup>5</sup>
36 Vf   400 mA

## Physical

trimless
diameter 75 mm   height 106 mm
0.51 kg

## Cutout

diameter 65 mm
min. ceiling thickness 9 mm   max. ceiling thickness 25 mm
recessed depth 200 mm

<sup>1</sup> oval lens BO 45 007-1965880  
<sup>2</sup> wallwasher lens BO 45 007-1965780  
<sup>3</sup> soft lens BO 45 007-1965980  
<sup>4</sup> Value of containing product at full load (undimmed)  
<sup>5</sup> incl. consideration of optical losses & internal control unit losses

## Installation instructions



## Lighting calculator

