

# MOVE IN 45 flex round

trimless

063-8221417V 063-8812117 002-90726



Project / Type

Notes

Count / Date



## General

Ceiling   Semi-Recessed
tilt max 90°
rotation 360°
white   RAL 9016 <sup>1</sup>
Mounting set traffic white
IP20
406 lm
fixture 59 lm/W <sup>2</sup>

## LED

2700 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 99   R <sub>r</sub> : 91   R <sub>(f-15)</sub> : 89
MR 0.54   MDER 0.49

## Optical

super spot   beam angle 8°
PstLM ≤ 1.0 <sup>3</sup>   SVM ≤ 0.4 <sup>3</sup>


## Electrical

non DIM
PC2   220-240 V
system 9.2 W   fixture 6.9 W
11 Vf   600 mA

## Physical

trimless
diameter 75 mm   height 106 mm
0.52 kg


## Light distribution



super spot 8°

h (m)	E0° (lx)	ø (m)
1	14200	0.14
2	3500	0.28
3	1600	0.41
4	900	0.55
5	600	0.69

## Product drawing



## Cutout

diameter 65 mm
min. ceiling thickness 9 mm   max. ceiling thickness 25 mm
recessed depth 200 mm

<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

