

MOVE IN 45 round

trim

063-8121516M 063-8822117 002-90724



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Semi-Recessed _____

brushed aluminium _____

Mounting set traffic white _____

IP20 _____

1270 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 100 , R_f: 91 , R₍₁₋₁₅₎: 88 _____

MR 0.59 _____

MDER 0.53 _____

Optical

medium _____

beam angle 24° _____

PstLM ≤ 1.0 ¹ _____

SVM ≤ 0.4 ¹ _____

Electrical

non DIM _____

15.9 W _____

PC2 220-240V _____

80 lm/W _____

Physical

trim _____

diameter 77 mm _____

height 107 mm _____

0.44 kg _____

Cutout

diameter 65 mm _____

min. ceiling thickness 2 mm _____

max. ceiling thickness 25 mm _____

recessed depth 200 mm _____

¹ Value of containing product at full load (undimmed)

Light distribution



| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 6120 | 0.43 |
| 2 | 1530 | 0.86 |
| 3 | 680 | 1.30 |
| 4 | 380 | 1.73 |
| 5 | 240 | 2.16 |

Product drawing



Installation instructions



Lighting calculator

