

MOVE IN 32 round

trim

063-8111514S 063-8821118 002-90743



| |
|----------------|
| Project / Type |
| Notes |
| Count / Date |



General

| |
|------------------------------|
| Ceiling , Semi-Recessed |
| chrome |
| Mounting set jet black |
| IP20 |
| 800 lm |
| fixture 91 lm/W ¹ |

LED

| |
|---|
| 3000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 100 , R _f : 91 , R _{f(1-5)} : 88 |
| MR 0.59 |
| MDER 0.53 |

Optical

| |
|--------------------------|
| spot |
| beam angle 18° |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Electrical

| |
|---------------|
| DALI-2 |
| 220-240 V |
| system 11.7 W |
| fixture 8.7 W |
| 36 Vf |
| 250 mA |
| PC2 |
| 1 DALI Addr. |

Physical


| |
|----------------|
| trim |
| diameter 65 mm |
| height 93 mm |
| 0.53 kg |

Cutout

| |
|------------------------------|
| diameter 54 mm |
| min. ceiling thickness 2 mm |
| max. ceiling thickness 25 mm |
| recessed depth 140 mm |

¹ incl. consideration of optical losses & internal control unit losses
² Value of containing product at full load (undimmed)

Light distribution



spot 18°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 6060 | 0.32 |
| 2 | 1510 | 0.63 |
| 3 | 670 | 0.95 |
| 4 | 380 | 1.27 |
| 5 | 240 | 1.58 |

Product drawing



Installation instructions



Lighting calculator

