

MOVE IN 32 round

trim

063-8111514M 063-8821117 002-90742



Project / Type
Notes
Count / Date



General

Ceiling , Semi-Recessed
chrome
Mounting set traffic white
IP20
833 lm
fixture 95 lm/W ¹

LED

3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 100 , R _f : 91 , R _{f(1-5)} : 88
MR 0.59
MDER 0.53

Optical

medium
beam angle 24°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical

non DIM
220-240 V
system 11.7 W
fixture 8.7 W
36 Vf
250 mA
PC2

Physical


trim
diameter 65 mm
height 93 mm
0.38 kg

Cutout

diameter 54 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 110 mm

¹ incl. consideration of optical losses & internal control unit losses
² Value of containing product at full load (undimmed)

Light distribution



h (m)	E0° (lx)	ø (m)
1	4430	0.42
2	1110	0.83
3	490	1.25
4	280	1.67
5	180	2.09

Product drawing



Installation instructions



Lighting calculator

