

MOVE IN 32 round

trimless

063-8111514M 063-8811117 002-90743



Project / Type

Notes

Count / Date



General

Ceiling | Semi-Recessed
chrome
Mounting set traffic white
IP20
852 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
 $R_g: 99$ | $R_f: 90$ | $R_{t(1-15)}: 87$
MR 0.6 | MDER 0.54

Optical

medium | beam angle 24°
 $P_{stLM} \leq 1.0^1 2^3 4$ | $SVM \leq 0.4^1 2^3 4$

Electrical

DALI-2 | 1 DALI Addr.
PC2 | 220-240 V
system 11.6 W | fixture 8.7 W
fixture 98 lm/W⁵
36 Vf | 250 mA


Physical

trimless
diameter 63 mm | height 92 mm
0.5 kg

Cutout

diameter 54 mm
min. ceiling thickness 9 mm | max. ceiling
thickness 25 mm
recessed depth 110 mm


Light distribution



medium 24°

h (m)	EO° (lx)	ø (m)
1	4530	0.42
2	1130	0.83
3	500	1.25
4	280	1.67
5	180	2.09

Product drawing



¹ soft lens BO 32 007-1965960 ² oval lens BO 32 007-1965860
³ wallwasher lens BO 32 007-1965760
⁴ Value of containing product at full load (undimmed)
⁵ incl. consideration of optical losses & internal control unit losses

Installation instructions



Lighting calculator

