

# MOVE IN 32 round

trim

063-8111416S 063-8821117 002-90743



Project / Type	
Notes	
Count / Date	



## General

Ceiling , Semi-Recessed
brushed aluminium
Mounting set traffic white
IP20
754 lm

## LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>r</sub> : 91 , R <sub>(1-15)</sub> : 89
MR 0.53
MDER 0.48

## Optical

spot
beam angle 18°
PstLM ≤ 1.0 <sup>1</sup>
SVM ≤ 0.4 <sup>1</sup>

## Electrical

DALI-2
11.6 W
PC2 220-240V
65 lm/W
1 DALI Addr.

## Physical


trim
diameter 65 mm
height 93 mm
0.48 kg

## Cutout

diameter 54 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 140 mm

<sup>1</sup> Value of containing product at full load (undimmed)



## Light distribution



spot 18°

h (m)	E0° (lx)	ø (m)
1	5710	0.32
2	1430	0.63
3	630	0.95
4	360	1.27
5	230	1.58

## Product drawing



## Installation instructions



## Lighting calculator

