

# MOVE IN 32 round

trim

063-8111416F 063-8821118 002-90742



|                |
|----------------|
| Project / Type |
| Notes          |
| Count / Date   |



## General

|                              |
|------------------------------|
| Ceiling , Semi-Recessed      |
| brushed aluminium            |
| Mounting set jet black       |
| IP20                         |
| 750 lm                       |
| fixture 86 lm/W <sup>1</sup> |

## LED

|  |
|--|
| 2700 K   |
| CRI ≥ 90   |
| L80 / 50000 h  |
| initial MacAdam ≤ 2 SDCM   |
| R <sub>g</sub> : 99 , R <sub>f</sub> : 91 , R <sub>(1-15)</sub> : 89 |
| MR 0.53  |
| MDER 0.48  |

## Optical

|                          |
|--------------------------|
| flood                    |
| beam angle 34°           |
| PstLM ≤ 1.0 <sup>2</sup> |
| SVM ≤ 0.4 <sup>2</sup>   |

## Electrical

|               |
|---------------|
| non DIM       |
| 220-240 V     |
| system 11.6 W |
| fixture 8.7 W |
| 36 Vf         |
| 250 mA        |
| PC2           |

## Physical


|                |
|----------------|
| trim           |
| diameter 65 mm |
| height 93 mm   |
| 0.38 kg        |

## Cutout

|                              |
|------------------------------|
| diameter 54 mm               |
| min. ceiling thickness 2 mm  |
| max. ceiling thickness 25 mm |
| recessed depth 110 mm        |

<sup>1</sup> incl. consideration of optical losses & internal control unit losses  
<sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



## flood 34°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 2450     | 0.61  |
| 2     | 610      | 1.21  |
| 3     | 270      | 1.82  |
| 4     | 150      | 2.42  |
| 5     | 100      | 3.03  |

## Product drawing



## Installation instructions



## Lighting calculator

