

MOVE IN 32 round

trim

063-8111416F 063-8821117 002-90742



Project / Type
Notes
Count / Date



General

Ceiling , Semi-Recessed
brushed aluminium
Mounting set traffic white
IP20
750 lm
fixture 86 lm/W ¹

LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 99 , R _f : 91 , R ₍₁₋₁₅₎ : 89
MR 0.53
MDER 0.48

Optical

flood
beam angle 34°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical

non DIM
220-240 V
system 11.6 W
fixture 8.7 W
36 Vf
250 mA
PC2

Physical

trim
diameter 65 mm
height 93 mm
0.38 kg

Cutout

diameter 54 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 110 mm

¹ incl. consideration of optical losses & internal control unit losses
² Value of containing product at full load (undimmed)

Light distribution



flood 34°

h (m)	E0° (lx)	ø (m)
1	2450	0.61
2	610	1.21
3	270	1.82
4	150	2.42
5	100	3.03

Product drawing



Installation instructions



Lighting calculator

