

# MOVE IN 32 round

trimless

063-8111416F 063-8811117 002-90742



Project / Type

Notes

Count / Date



## General

Ceiling , Semi-Recessed

brushed aluminium

Mounting set traffic white

IP20

750 lm

## LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89

MR 0.53

MDER 0.48

## Optical

flood

beam angle 34°

PstLM ≤ 1.0 <sup>1</sup>

SVM ≤ 0.4 <sup>1</sup>

## Electrical

non DIM

11.6 W

PC2 220-240V

65 lm/W

## Physical

trimless

diameter 63 mm

height 92 mm

0.13 kg

## Cutout

diameter 54 mm

min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 110 mm

<sup>1</sup> Value of containing product at full load (undimmed)

## Light distribution



flood 34°

h (m)	E0° (lx)	ø (m)
1	2450	0.61
2	610	1.21
3	270	1.82
4	150	2.42
5	100	3.03

## Product drawing



## Installation instructions



## Lighting calculator

