

# MOVE IN 32 round

trim

063-8111414F 063-8821118 002-90743



Project / Type

Notes

Count / Date



### General

Ceiling , Semi-Recessed

chrome

Mounting set jet black

IP20

750 lm

### LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.53

MDER 0.48

### Optical

flood

beam angle 34°

PstLM ≤ 1.0 <sup>1</sup>

SVM ≤ 0.4 <sup>1</sup>

### Electrical

DALI-2

11.6 W

PC2 220-240V

65 lm/W

1 DALI Addr.

### Physical

trim

diameter 65 mm

height 93 mm

0.3 kg

### Cutout

diameter 54 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 140 mm

<sup>1</sup> Value of containing product at full load (undimmed)


### Light distribution



flood 34°

h (m)	E0° (lx)	ø (m)
1	2450	0.61
2	610	1.21
3	270	1.82
4	150	2.42
5	100	3.03

### Product drawing



### Installation instructions



### Lighting calculator

