

# MOVE IN 32 round

trim

063-8111414F 063-8821117 002-90743



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Semi-Recessed \_\_\_\_\_

chrome \_\_\_\_\_

Mounting set traffic white \_\_\_\_\_

IP20 \_\_\_\_\_

750 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI  $\geq$  90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam  $\leq$  2 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.53 \_\_\_\_\_

MDER 0.48 \_\_\_\_\_

## Optical

flood \_\_\_\_\_

beam angle 34° \_\_\_\_\_

PstLM  $\leq$  1.0 <sup>1</sup> \_\_\_\_\_

SVM  $\leq$  0.4 <sup>1</sup> \_\_\_\_\_

## Electrical

DALI-2 \_\_\_\_\_

11.6 W \_\_\_\_\_

PC2 220-240V \_\_\_\_\_

65 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

## Physical

trim \_\_\_\_\_

diameter 65 mm \_\_\_\_\_

height 93 mm \_\_\_\_\_

0.3 kg \_\_\_\_\_

## Cutout

diameter 54 mm \_\_\_\_\_


min. ceiling thickness 2 mm \_\_\_\_\_

max. ceiling thickness 25 mm \_\_\_\_\_

recessed depth 140 mm \_\_\_\_\_

<sup>1</sup> Value of containing product at full load (undimmed)

## Light distribution



flood 34°

h (m)	E0° (lx)	ø (m)
1	2450	0.61
2	610	1.21
3	270	1.82
4	150	2.42
5	100	3.03

## Product drawing



## Installation instructions



## Lighting calculator



[063-8111414F 063-8821117 002-90743] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

04.05.2024