

SASSO 100 round downlight

trim 2 lamps

048-2700412W 048-2798318 002-90774



Project / Type _____

Notes _____

Count / Date _____



↑ IP20
↓ IP44

220-240V

X-PERT

X-PERT

General

Ceiling , Recessed _____

chrome _____

Mounting set jet black _____

front IP44 , back IP20 _____

4380 lm _____

LED

2700 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89 _____

MR 0.53 _____

MDER 0.48 _____

Optical

wide flood _____

beam angle 65° _____

≥65° <1500 cd/m² _____

PstLM ≤ 1.0 ¹ _____

SVM ≤ 0.4 ¹ _____

Electrical

non DIM _____

58 W _____

total insets 50 W _____

PC2 220-240V _____

76 lm/W _____

Physical

trim _____

length 218 mm _____

width 118 mm _____

height 75 mm _____

0.46 kg _____

Cutout

diameter 105 mm _____

length 205 mm _____


min. ceiling thickness 2 mm _____

max. ceiling thickness 25 mm _____

recessed depth 100 mm _____

¹ Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator

