

SQUADRO double-sided wallwasher

track
149-2220117B



Project / Type


Notes

Count / Date




Tracked spotlight in die cast aluminium with 2x2-lamp design; surface white powder coated; converter integrated into spotlight head; heat sink integrated into luminaire geometry for optimum thermal management and passive cooling of LEDs; with COB (Chip on Board) technology for maximum efficiency; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; Aisle spotlight 1x shelf / 1x wall floor washer with special, multi-free-form, facet effect surface reflectors for high precision light control; precise shelf and aisle zone lighting, optimum longitudinal glare control for high viewing comfort in the aisle zone; adjustable light modules (tiltable $+20^\circ$ to -10°); 350° rotatable; degree of protection IP20; IP 40 protection glass available as an accessory; accessories are listed separately; PC2 220-240V; incl. converter, non dimmable; adapter for toolless insertion or movement on a variety of 3-phase power tracks; including attachment for linear alignment of the spotlights; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Track

tilt min -10°

tilt max 20°

rotation 350°

white , RAL9016 ¹

IP20

9970 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

Optical

shelf / wall floor washer

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

non DIM

72 W

PC2 220-240V

138 lm/W

Physical

length 140 mm

width 150 mm

height 76 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions

