

SQUADRO double-sided wallwasher

track

149-2220117B



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track _____
 tilt min -10° _____
 tilt max 20° _____
 rotation 350° _____
 white , RAL9016 ¹ _____
 IP20 _____
 9970 lm _____

LED

4000 K _____
 CRI ≥ 90 _____
 L80 / 50000 h _____
 initial MacAdam ≤ 2 SDCM _____

Optical

shelf / wall floor washer _____
 PstLM ≤ 1.0 ² _____
 SVM ≤ 0.4 ² _____

Electrical

non DIM _____
 72 W _____
 PC2 220-240V _____
 138 lm/W _____


Physical

length 140 mm _____
 width 150 mm _____
 height 76 mm _____


Tracked spotlight in die cast aluminium with 2x2-lamp design; surface white powder coated; converter integrated into spotlight head; heat sink integrated into luminaire geometry for optimum thermal management and passive cooling of LEDs; with COB (Chip on Board) technology for maximum efficiency; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; Aisle spotlight 1x shelf / 1x wall floor washer with special, multi-free-form, facet effect surface reflectors for high precision light control; precise shelf and aisle zone lighting, optimum longitudinal glare control for high viewing comfort in the aisle zone; adjustable light modules (tiltable +20° to -10°); 350° rotatable; degree of protection IP20; IP 40 protection glass available as an accessory; accessories are listed separately; PC2 220-240V; incl. converter, non dimmable; adapter for toolless insertion or movement on a variety of 3-phase power tracks; including attachment for linear alignment of the spotlights; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



SQUADRO double-sided wallwasher

track

149-2220117B



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.977	0.94	0.905	0.871	0.838
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	33
B13	43
B16	53
B20	67
C10	53
C13	69
C16	85
C20	107

Optical accessories

IP40 PROTECTION GLASS

TYPE

2 x 2 lamps / double-sided

ARTICLE NUMBER(S)

049-2920010

