

NOBA 60 suspended

MOVE IT 10

030-6920535



Project / Type

Notes

Count / Date



Decorative pendant light inset made of aluminium; surface anodised gun metal; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;



General

Ceiling , Track Suspended

gun metal

IP20

903 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 100 , R_f: 91 , R_{f(1-5)}: 88

MR 0.59

MDER 0.53

Optical

Wide Flood

beam angle 67°

Electrical

DALI-2

8.1 W

PC3

111 lm/W

1 DALI Addr.


Physical

diameter 60 mm

height 60 mm

1500 mm


Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	858	1.31
2	215	2.63
3	95	3.94
4	54	5.26
5	34	6.57

Product drawing



Installation instructions



Lighting calculator

