

# NOBA 40 suspended

MOVE IT 10

030-6900533



Project / Type


Notes

Count / Date



Decorative pendant light inset made of aluminium; surface lacquered in brushed brass; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;


## Light distribution



wide flood 67°

| h (m) | EO° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 407      | 1.31  |
| 2     | 102      | 2.63  |
| 3     | 45       | 3.94  |
| 4     | 25       | 5.26  |
| 5     | 16       | 6.57  |

## Product drawing



## General

Ceiling , Track Suspended

brushed brass

IP20

428 lm

## LED

3000 K

CRI  $\geq 90$

L80 / 50000 h

initial MacAdam  $\leq 2$  SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-5)</sub>: 88

MR 0.59

MDER 0.53

## Optical

Wide Flood

beam angle 67°

## Electrical

DALI-2

3.5 W

PC3

122 lm/W

1 DALI Addr.

## Physical

diameter 40 mm

height 40 mm

1500 mm

## Installation instructions



## Lighting calculator

