

TARO 45 downlight

MOVE IT 10 round
030-6750433M



Project / Type _____

Notes _____

Count / Date _____



Cylindrical spotlight in aluminium; surface lacquered in brushed brass; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 24° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;



General

Ceiling / Wall , Track _____

brushed brass _____

IP20 _____

926 lm _____

LED

2700 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 99 , R_f: 91 , R_{1-15}: 89 _____

MR 0.53 _____

MDER 0.48 _____

Optical

Medium _____

beam angle 24° _____

Electrical

DALI-2 _____

11.0 W _____

PC3 _____

84 lm/W _____

1 DALI Addr. _____

Physical

diameter 45 mm _____

height 75 mm _____

Light distribution

