

TARO 32 downlight

MOVE IT 10 round
030-6740639S



Project / Type _____


Notes _____

Count / Date _____




Cylindrical spotlight in aluminium; surface anodised rose gold; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 18° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



h (m)	EO° (lx)	ø (m)
1	6250	0.32
2	1560	0.63
3	690	0.95
4	390	1.27
5	250	1.58

Product drawing



General

Ceiling / Wall | Track _____

rose gold _____

IP20 _____

825 lm _____

LED

4000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 97 | R_f: 90 | R_{t(1-15)}: 89 _____

MR 0.81 | MDER 0.74 _____

Optical

spot | beam angle 18° _____

PstLM $\leq 1.0^1 2^3 4$ | SVM $\leq 0.4^1 2^3 4$ _____

Electrical

DALI-2 | 1 DALI Addr. _____

PC3 | 48 V _____

fixture 9.6 W _____

fixture 86 lm/W ⁵ _____

Physical

diameter 32 mm | height 60 mm _____

¹ wallwasher lens BO 32 007-1965760
² oval lens BO 32 007-1965860 ³ soft lens BO 32 007-1965960
⁴ Value of containing product at full load (undimmed)
⁵ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

