

030-6740439M



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

rose gold

IP20

764 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

$R_q: 99$, $R_f: 91$, $R_{\{1-15\}}: 89$

MR 0.53

MDER 0.48

Optical

Medium

beam angle 24°

Electrical

DALI-2

9.6 W

PC3

80 lm/W

1 DALI Addr.

Physical

diameter 32 mm

height 60 mm




Cylindrical spotlight in aluminium; surface anodised rose gold; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 24° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

medium 24°

h (m)	E0° (lx)	ø (m)
1	4060	0.42
2	1020	0.83
3	450	1.25
4	250	1.67
5	160	2.09

Product drawing



Installation instructions

