

MOVE IT 10 square
030-6780433W



Project / Type

Notes

Count / Date



Ceiling / Wall | Track

rotation 360°

brushed brass

IP20

780 lm

optical inset 112 lm/W⁻¹

2700 K

CRI $\geq .90$

185 / 500

```
initial MacAddress
```

Initial MacAduall ≤ 5 SDCM
 B = 404 / B = 22 / B = 22

R_g: 101 | R_f: 90 | R_{1-15}: 88

MR 0.51 | MDER 0.46

wallwasher floor

$$\text{PstLM} \leq 1.0^2 \mid \text{SVM} \leq 0.4^2$$

DALI-2 | 1 DALI Addr.

PC3 | 48 V

fixture 9.3 W



optical inset 7.0 W

diameter 45 mm | height 75 mm

0.14 kg

Cylindrical spotlight in aluminium; surface lacquered in brushed brass; 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; with specially computed, asymmetrical reflector for homogeneous lighting intensity; no multiple shadows; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Product drawing

¹ incl. consideration of optical losses² Value of containing product at full load (undimmed)

Installation instructions

