

# TARO 45 downlight

MOVE IT 10 round  
030-6750539F



Project / Type

Notes

Count / Date



Cylindrical spotlight in aluminium; surface anodised rose gold; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 36° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;



General

Ceiling / Wall , Track

rose gold

IP20

1010 lm

LED

3000 K

CRI  $\geq 90$

L80 / 50000 h

initial MacAdam  $\leq 2$  SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 88

MR 0.59

MDER 0.53

Optical

Flood

beam angle 36°

Electrical

DALI-2

11.0 W

PC3

92 lm/W


1 DALI Addr.

Physical

diameter 45 mm

height 75 mm

## Light distribution



flood 36°		
h (m)	E0° (lx)	ø (m)
1	3010	0.65
2	750	1.29
3	330	1.94
4	190	2.59
5	120	3.23

## Product drawing



## Installation instructions

