

# TARO 32 downlight

MOVE IT 10 square  
030-6700639S



Project / Type

Notes

Count / Date



Cylindrical spotlight in aluminium; surface anodised rose gold; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 18° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;



### General

Ceiling / Wall , Track

rose gold

IP20

825 lm

### LED

4000 K

CRI  $\geq 90$

L80 / 50000 h

initial MacAdam  $\leq 2$  SDCM

R<sub>g</sub>: 97 , R<sub>f</sub>: 90 , R<sub>(1-15)</sub>: 89

MR 0.81

MDER 0.74

### Optical

Spot

beam angle 18°

### Electrical

DALI-2

9.6 W

PC3

86 lm/W

1 DALI Addr.

### Physical

diameter 32 mm


height 60 mm

### Light distribution



spot 18°		
h (m)	E0° (lx)	ø (m)
1	6250	0.32
2	1560	0.63
3	690	0.95
4	390	1.27
5	250	1.58

### Product drawing



### Installation instructions

