

030-6700539F



Project / Type

Notes

Count / Date



Ceiling / Wall | Track

rose gold

IP20

774 lm

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_Q: 100 | R_f: 91 | R_{1-15}: 89

MR 0.59 | MDER 0.53

flood | beam angle 34°

$$\text{PstLM} \leq 1.0^{1\ 2\ 3\ 4} \mid \text{SVM} \leq 0.4^{1\ 2\ 3\ 4}$$

DALI-2 | 1 DALI Addr.

PC3 | 48 V

fixture 9.6 W

fixture 81 lm/W⁵


diameter 32 mm | height 60 mm

Cylindrical spotlight in aluminium; surface anodised rose gold; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 34° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

flood 34°

h (m)	E0° (lx)	ø (m)
1	2520	0.61
2	630	1.21
3	280	1.82
4	160	2.42
5	100	3.03

Product drawing



Installation instructions



¹ wallwasher lens BO 32 007-1965760

² oval lens BO 32 007-1965860 ³ soft lens BO 32 007-1965960⁴ Value of containing product at full load (undimmed)⁵ incl. consideration of optical losses, internal control unit losses & operating device efficiency