

TARO 32 downlight

MOVE IT 10 square
030-6700535S



Project / Type _____


Notes _____

Count / Date _____



Cylindrical spotlight in aluminium; surface anodised gun metal; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 18° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;


Light distribution



spot 18°

h (m)	E0° (lx)	ø (m)
1	5890	0.32
2	1470	0.63
3	650	0.95
4	370	1.27
5	240	1.58

Product drawing



General

Ceiling / Wall | Track _____

gun metal _____

IP20 _____

778 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 100 | R_f: 91 | R_{1-15}: 89 _____

MR 0.59 | MDER 0.53 _____

Optical

spot | beam angle 18° _____

PstLM ≤ 1.0 ^{1 2 3 4} | SVM ≤ 0.4 ^{1 2 3 4} _____

Electrical

DALI-2 | 1 DALI Addr. _____

PC3 | 48 V _____

fixture 9.6 W _____

fixture 81 lm/W⁵ _____

Physical

diameter 32 mm | height 60 mm _____

0.87 kg _____

¹ soft lens BO 32 007-1965960
² wallwasher lens BO 32 007-1965760
³ oval lens BO 32 007-1965860
⁴ Value of containing product at full load (undimmed)
⁵ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

