

TILA 32 adjustable

MOVE IT 10
030-6560639S



Project / Type


Notes

Count / Date



Decorative spotlight inset made of aluminium; surface anodised rose gold; 365° rotatable and 135° tiltable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; high quality reflector; precise radiation characteristic with 18° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



spot 18°		
h (m)	EO° (lx)	ø (m)
1	6440	0.32
2	1610	0.63
3	720	0.95
4	400	1.27
5	260	1.58

Product drawing



General

Ceiling / Wall | Track

tilt max 135°

rotation 365°

rose gold

IP20

851 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 | R_f: 90 | R_{t(1-15)}: 89

MR 0.81 | MDER 0.74

Optical

spot | beam angle 18°

PstLM ≤ 1.0 ^{1 2 3 4} | SVM ≤ 0.4 ^{1 2 3 4}

Electrical

DALI-2 | 1 DALI Addr.

PC3 | 48 V

fixture 9.7 W

fixture 88 lm/W⁵

Physical

diameter 32 mm | height 120 mm

¹ wallwasher lens BO 32 007-1965760
² oval lens BO 32 007-1965860 ³ soft lens BO 32 007-1965960
⁴ Value of containing product at full load (undimmed)
⁵ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

