

TILA 32 adjustable

MOVE IT 10


030-6560633S



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling / Wall , Track _____
 tilt max 135° _____
 rotation 365° _____
 brushed brass _____
 IP20 _____
 851 lm _____

LED

4000 K _____
 CRI ≥ 90 _____
 L80 / 50000 h _____
 initial MacAdam ≤ 2 SDCM _____
 R_g: 97 , R_f: 90 , R₍₁₋₁₅₎: 89 _____
 MR 0.81 _____
 MDER 0.74 _____

Optical

Spot _____
 beam angle 18° _____

Electrical


DALI-2 _____
 9.7 W _____
 PC3 _____
 88 lm/W _____
 1 DALI Addr. _____

Physical

diameter 32 mm _____
 height 120 mm _____

Decorative spotlight inset made of aluminium; surface lacquered in brushed brass; 365° rotatable and 135° tiltable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; high quality reflector; precise radiation characteristic with 18° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;


Light distribution



spot 18°

h (m)	E0° (lx)	ø (m)
1	6440	0.32
2	1610	0.63
3	720	0.95
4	400	1.27
5	260	1.58

Product drawing



Installation instructions

