

# TILA 22 suspended

MOVE IT 10

030-6630433S



Project / Type

Notes

Count / Date



## General

Ceiling , Track Suspended

brushed brass

IP20

308 lm

optical inset 60 lm/W<sup>1</sup>

## LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 89

MR 0.53

MDER 0.48

## Optical

spot

beam angle 15°

PstLM ≤ 1.0<sup>2</sup>

SVM ≤ 0.4<sup>2</sup>

## Electrical

DALI-2

48 V

fixture 5.7 W

optical inset 5.1 W

PC3

1 DALI Addr.

## Physical

diameter 22 mm

height 100 mm

1500 mm

<sup>1</sup> incl. consideration of optical losses


<sup>2</sup> Value of containing product at full load (undimmed)

## Lighting calculator



Decorative pendant light inset made of aluminium; surface lacquered in brushed brass; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; high quality reflector; precise radiation characteristic with 15° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

## Light distribution



spot 15°

h (m)	E0° (lx)	ø (m)
1	2880	0.27
2	720	0.54
3	320	0.81
4	180	1.08
5	120	1.35

## Product drawing

