

# TILA 32 adjustable

MOVE IT 10  
030-6560439M



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

tilt max 135°

rotation 365°

rose gold

IP20

788 lm

optical inset 90 lm/W<sup>1</sup>

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>{1-15}</sub>: 89

MR 0.53

MDER 0.48

Optical

medium

beam angle 24°

P<sub>stLM</sub> ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

Electrical

DALI-2

48 V

fixture 9.7 W

optical inset 8.7 W

PC3

1 DALI Addr.

Physical

diameter 32 mm


height 120 mm

0.19 kg

<sup>1</sup> incl. consideration of optical losses


<sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



medium 24°		
h (m)	E0° (lx)	ø (m)
1	4190	0.42
2	1050	0.83
3	470	1.25
4	260	1.67
5	170	2.09

## Product drawing



## Installation instructions

