

TILA 32 adjustable

MOVE IT 10
030-6560435M



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

tilt max 135°

rotation 365°

gun metal

IP20

788 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_f: 91 , R₍₁₋₁₅₎: 89

MR 0.53

MDER 0.48

Optical

Medium

beam angle 24°

Electrical

DALI-2

9.7 W

PC3

81 lm/W

1 DALI Addr.


Physical

diameter 32 mm

height 120 mm


Decorative spotlight inset made of aluminium; surface anodised gun metal; 365° rotatable and 135° tiltable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; high quality reflector; precise radiation characteristic with 24° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



medium 24°			
h (m)	E0° (lx)	ø (m)	
1	4190	0.42	
2	1050	0.83	
3	470	1.25	
4	260	1.67	
5	170	2.09	

Product drawing



Installation instructions

