

TILA 16 suspended

MOVE IT 10

030-6610433F



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track Suspended _____

brushed brass _____

IP20 _____

205 lm _____

optical inset 77 lm/W¹ _____

LED

2700 K _____

CRI ≥ 90 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 , R_f: 91 , R_{f(1-15)}: 89 _____

MR 0.54 _____

MDER 0.49 _____

Optical

flood _____

beam angle 31° _____

PstLM ≤ 1.0² _____

SVM ≤ 0.4² _____

Electrical

DALI-2 _____

48 V _____

fixture 3.3 W _____

optical inset 2.6 W _____

PC3 _____

1 DALI Addr. _____

Physical

diameter 16 mm _____


height 600 mm _____

0.18 kg _____

1500 mm _____

¹ incl. consideration of optical losses
² Value of containing product at full load (undimmed)


Light distribution



flood 31°

h (m)	E0° (lx)	ø (m)
1	681	0.56
2	170	1.12
3	76	1.67
4	43	2.23
5	27	2.79

Product drawing



Installation instructions



Lighting calculator



TILA 16 suspended

MOVE IT 10

030-6610433F



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.97	0.94	0.91	0.88	0.85
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Mounting accessories

HOOK

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic white	16	030-1000017
jet black	16	030-1000018

