

TILA 16 suspended

MOVE IT 10
030-6600639M



Project / Type


Notes

Count / Date




Decorative pendant light inset made of aluminium; surface anodised rose gold; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; high quality reflector; precise radiation characteristic with 23° beam; no multiple shadows; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



medium 23°			
h (m)	EO° (lx)	ø (m)	
1	769	0.41	
2	192	0.81	
3	85	1.22	
4	48	1.62	
5	31	2.03	

Product drawing



General

Ceiling , Track Suspended

rose gold

IP20

161 lm

LED

4000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 94 , R_f: 87 , R₍₁₋₁₅₎: 90

MR 0.86

MDER 0.78

Optical

Medium

beam angle 23°

Electrical

DALI-2

3.3 W

PC3

49 lm/W

1 DALI Addr.

Physical

diameter 16 mm

height 80 mm

1500 mm

Installation instructions



Lighting calculator

