

TILA 16 adjustable

MOVE IT 10
030-6500439F



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling / Wall , Track _____

tilt max 135° _____

rotation 365° _____

rose gold _____

IP20 _____

205 lm _____

optical inset 77 lm/W¹ _____

LED

2700 K _____

CRI ≥ 90 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89 _____

MR 0.54 _____

MDER 0.49 _____

Optical

flood _____

beam angle 31° _____

P_{stLM} ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

48 V _____

fixture 3.3 W _____

optical inset 2.6 W _____

PC3 _____

1 DALI Addr. _____


Physical

diameter 16 mm _____

height 80 mm _____


¹ incl. consideration of optical losses
² Value of containing product at full load (undimmed)

Light distribution



flood 31°			
h (m)	E0° (lx)	ø (m)	
1	681	0.56	
2	170	1.12	
3	76	1.67	
4	43	2.23	
5	27	2.79	

Product drawing



Installation instructions



TILA 16 adjustable

MOVE IT 10
030-6500439F



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.97	0.94	0.91	0.88	0.85
LSF	1	1	1	1	1

MF

MF

LMF^a

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF^a

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Factor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Mounting accessories

HOOK

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic white	16	030-1000017
jet black	16	030-1000018

