

# SASSO 40 wallwasher/ floor

PROFILES 40 2 lamps  
042-0620138W



Project / Type

Notes

Count / Date



## General

Ceiling , Recessed

rotation 360°

black , RAL 9005 <sup>1</sup>

IP20

1670 lm

## LED

4000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 92 , R<sub>f(1-15)</sub>: 90

MR 0.81

MDER 0.74

## Optical

wallwasher floor

beam angle 53°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2

220-240 V

system 16.4 W

system 102 lm/W<sup>3</sup>

PC1

## Physical

length 300 mm

width 45 mm

height 105 mm

adapter 300 mm

## Cutout

diameter 56 mm

recessed depth 120 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

<sup>3</sup> incl. consideration of optical losses, internal control unit losses  
& operating device efficiency


## Installation instructions



## Lighting calculator



## Light distribution



## Product drawing

