

SASSO 40 wallwasher/ floor

PROFILES 40 2 lamps
042-0620137W



Project / Type	
Notes	
Count / Date	



--	--	--	--

General
Ceiling , Recessed
rotation 360°
RAL Traffic white , RAL 9016 ¹
IP20
1320 lm

LED
4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 94 , R _r : 87 , R _{t(1-15)} : 86
MR 0.8
MDER 0.72

Optical
wallwasher floor
beam angle 53°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²


Electrical
DALI-2
15.9 W
total insets 13.5 W
PC1 220-240V
83 lm/W

Physical
length 300 mm
width 45 mm
height 105 mm
0.24 kg
300 (adapter) mm


Cutout
diameter 56 mm
recessed depth 120 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator



SASSO 40 wallwasher/ floor

PROFILES 40 2 lamps
042-0620137W



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.89	0.85	0.82
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	36
B13	47
B16	58
C10	36
C13	78
C16	58

