

SASSO 40 wallwasher/ floor

PROFILES 40 2 lamps
042-0620037W



Project / Type

Notes

Count / Date



General

Ceiling , Recessed

rotation 360°

RAL Traffic white , RAL 9016 ¹

IP20

1320 lm

LED

3000 K

CRI \geq 90

L80 / 50000 h

initial MacAdam \leq 3 SDCM

R_g: 97 , R_r: 91 , R_{f(1-15)}: 89

MR 0.6

MDER 0.54

Optical

wallwasher floor

beam angle 53°

PstLM \leq 1.0 ²

SVM \leq 0.4 ²

Electrical

DALI-2

15.9 W

total insets 13.5 W

PC1 220-240V

83 lm/W

Physical

length 300 mm

width 45 mm

height 105 mm

0.24 kg

300 (adapter) mm


Cutout

diameter 56 mm


recessed depth 120 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



SASSO 40 wallwasher/ floor

PROFILES 40 2 lamps
042-0620037W



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.89	0.85	0.82
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	36
B13	47
B16	58
C10	36
C13	78
C16	58

