

# SASSO 40 wallwasher/ floor

PROFILES 40 1 lamp  
042-0520138W



Project / Type

Notes

Count / Date



**General**  
Ceiling , Recessed  
rotation 360°  
black , RAL9005 <sup>1</sup>  
IP20  
645 lm

**LED**  
4000 K  
CRI ≥ 90  
L80 / 50000 h  
initial MacAdam ≤ 3 SDCM  
R<sub>g</sub>: 94 , R<sub>r</sub>: 87 , R<sub>t(1-15)</sub>: 86  
MR 0.8  
MDER 0.72

**Optical**  
wallwasher floor  
beam angle 53°  
PstLM ≤ 1.0 <sup>2</sup>  
SVM ≤ 0.4 <sup>2</sup>


**Electrical**  
DALI-2  
9.0 W  
PC1 220-240V  
72 lm/W

**Physical**  
length 300 mm  
width 45 mm  
height 105 mm  
0.24 kg  
300 (adapter) mm


**Cutout**  
diameter 56 mm  
recessed depth 120 mm

Spotlight made of aluminium; 1 lamp; cylindrical spotlight head; surface black powder coated; spotlight head 360° rotatable; spotlight can be installed without tools in MINO 40 system or FRAME 40 system; converter integrated in the power track adapter; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; good glare control through recessed light point level; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

